

AHD DVR (NHD-2104 HL)

NHD-2104HL model AHD DVR developed by S.D.S. Da Technology Co., Ltd. and branded as the only govt. registered security system brand " **NS Vision** " with recommendation of **NS International**.

This product support cloud and dual-stream technology, adopting High Definition compression algorithm and Linux real-time operating system. Video output transmit via HDMI and VGA ports with features of excellent connection rate, good transmission effect, easy operation, etc. This is optimal product of NS Vision for network remote monitoring, integrated with various practical functions, such as audio and video playback, network transmission, and alarm management. It could be widely used in school, small factory/office, bank, traffic, community, warehouse, water conservancy and other fields.



Key features:

- ✚ Cloud Technology
- ✚ Double level user anagement
- ✚ Supports live view, parameter setting and download playback video via network.
- ✚ Supports remote view through CMS, iOS and Android Apps.
- ✚ Motion detection, privacy masking, Email-alert, Time auto synchronize, digital zoom function,etc

Specification:

Model/Spec.		NHD-2104 HL
Input	Video Input	04 CH 720P
Output	HDMI	1CH, Resolution: 1920×1080/60Hz, 1440×900/60Hz, 1366×768/60Hz, 1280×1024/60Hz, 1280×800/60Hz, 1024×768/60Hz
	VGA	1CH, Resolution: 1920×1080/60Hz, 1440×900/60Hz, 1366×768/60Hz, 1280×1024/60Hz, 1280×800/60Hz, 1024×768/60Hz
	Frame rate	Main Stream
	Audio Output	N/A
Encoding	Record	1280×720/ 768×432/ 704×576
	Video Encoding	4 CH 720P
	Sync Playback	4CH 7200P
Record	Record/Snapshot	Manual Record/Snapshot, Scheduled, Motion Detection Record/Snapshot, Alarm Record/Snapshot, Playback Snapshot
	Playback Mode	Time List & Event Playback
	Backup Mode	Video Backup & Picture Backup
HDD	Type	1 x SATA Interface
	Capacity	up to 4TB
External	Audio Intercom	N/A
	Net Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
	Serial Interface	1 RS-485 interface (reserved)
	USB Interface	2 x USB 2.0 Interface
	Alarm In	1 CH(NONC)
	Alarm Output	Software
Network	Protocol	TCP/IP, DHCP, UDP, SMTP, NTP, P2P,
General	Temperature	-10°C~+55°C
	Humidity	10%~90%
	Power Supply	ATX Power, Specified 250W
	Power	≤15W
	Language	Multi-Languages
	Size (W×H×D)	325×60×225mm
	Weight	≤2.23kg